



# MEKASTER Electronic Torque Wrench



## Features

- Selectable Units: cNm, Nm, kgfm, kgfcm, ozins, lbins, lbft.
- Accuracy: better than 1% of the Reading LH & RH 10% to max. of Scales.
- Reading starts from 2% of maximum.
- Modes of Operation: 3 (Trac, Preset, Units).
- Large alphanumeric LCD display with backlight.
- Audible & Visual Alarms and Signals incorporated.
- Automatic Zero Point setting.
- Electronic Calibration by Date /or by number of measurements taken.
- Rechargeable batteries with lifespan up to 200 hrs.
- Automatic Power Down.
- Over – Torque warning system
- Menu Driven controls.



## Additional features in programmable models

- Enhanced Modes of Operation (Upload, Set, Backlite)
- Programming of Minimum and Maximum tolerances
- Storage of Measurements: 2094 values
- Direct Download



## MODELS Torque Range

Standard	Programmable	Nm	In Lbs	Ft lbs	Square Drive Inch	Length mm	Weight Kg
E3020	P3020	2-20	17-177	1.4-14	1/4	410	0.67
E3135	P3135	13.5-135	-	9.9 - 99	3/8	415	0.73
E3250	P3250	25-250	-	18 -180	1/2	570	1.2
E3340	P3340	34 - 340	-	25 - 250	1/2	625	1.3

Accuracy  $\pm$  1% of Reading.

Specially made for Mekaster in Ireland